



S.C. PRIMA S.R.L. Botoșani

Automatizari instalatii transport fluide

Echipamente pentru abur,aer,apa,produse petrochimice

Robineti industriali,pompe,produse inox

Echipamente tratare apa

Nr. 748 / 24.11.2011

VENTIL ELECTROMAGNETIC ABUR SLA



SLA

- Ventil electromagnetic cu piston 2/2
- Normal Inchis
- Presiunea de lucru maxima 25 bari
- Presiunea minima : 0,5 bari
- Temperature maxima de 185 °C.
- Material corp: Alamă
- Piston : PTFE
- Conexiune : Filet Interior
- Tensiuni disponibile: 230Vca, 24V CA, 24 V DC
- Mediul de lucru:
- Abur
- Dimensiuni: 1/2" -1

Nr.Inreg.Com.J07/260/1998

C.I.F:RO 10825641

IBAN:RO07WBAN2511000007500011 INTESA SAN PAOLO BANK BT

IBAN:RO66TREZ1165069XXX004921 TREZORERIA BOTOSANI

Str.Primaverii, Nr.2,Sc.B,Ap.2

Cod710070

Tel./Fax:0231.580535 M:0746.033.149

E-mail:primabotosani@yahoo.com

Web:www.primabt.ro

Web:www.robineti-proces.ro



S.C. PRIMA S.R.L. Botoșani

Automatizari instalatii transport fluide

Echipamente pentru abur,aer,apa,produse petrochimice

Robineti industriali ,pompe,produse inox

Echipamente tratare apa

Nr. 748 / 24.11.2011

Specifications

| Port size | Orifice (mm) | CV value | Min. Pressure | Pressure difference(bar) | | | | | | | | Max. Temperature (°C) | Power | | Model 220VAC | | |
|-----------|--------------|----------|---------------|--------------------------|----|-------------------------|----|-------------------|----|-------|-----|-----------------------|-------|-------------|--------------|-------|---------------------|
| | | | | Max.Working Pressure | | | | | | | | | AC DC | AC 220 | DC 24V | Brass | Stainless Steel 304 |
| | | | | Air, Gas | | Water, hot water liquid | | Light Oil < 20CST | | Steam | | | | | | | |
| AC | DC | AC | DC | AC | DC | AC | DC | AC | DC | | | | | | | | |
| 1/8" | 2.5 | 0.23 | 0 | 8 | 8 | 8 | 8 | 6 | 6 | 10 | 180 | 22 | 13 | SLA06T-2.5L | -- | | |
| | 2.5 | 0.23 | 0 | 13 | 13 | 13 | 13 | 7 | 7 | 10 | 110 | 22 | 13 | SLA06V-2.5L | -- | | |
| | 4.5 | 0.6 | 0 | 7 | 4 | 7 | 4 | 4 | 4 | 7 | 165 | 22 | 13 | SLA06T-4.5L | -- | | |
| | 4.5 | 0.6 | 0 | 7 | 4 | 7 | 4 | 4 | 4 | 7 | 110 | 22 | 13 | SLA06V-4.5L | -- | | |
| 1/4" | 2.5 | 0.23 | 0 | 7 | 4 | 7 | 4 | 4 | 4 | 10 | 180 | 22 | 13 | SLA08T-2.5L | -- | | |
| | 2.5 | 0.23 | 0 | 13 | 13 | 13 | 13 | 7 | 7 | 10 | 110 | 22 | 13 | SLA08V-2.5L | -- | | |
| | 4.5 | 0.6 | 0 | 7 | 4 | 7 | 4 | 4 | 4 | 7 | 165 | 22 | 13 | SLA08T-4.5L | -- | | |
| | 4.5 | 0.6 | 0 | 7 | 4 | 7 | 4 | 4 | 4 | 7 | 110 | 22 | 13 | SLA08V-4.5L | -- | | |
| 3/8" | 15 | 4.5 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | SLA10V-15L | SLA10V-15LS2 | | |
| | 15 | 4.5 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | SLA10T-15L | SLA10T-15LS2 | | |
| 1/2" | 15 | 4.5 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | SLA15V | SLA15VS2 | | |
| | 15 | 4.5 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | SLA15T | SLA15TS2 | | |
| 3/4" | 20 | 9.0 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | SLA20V | SLA20VS2 | | |
| | 20 | 9.0 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | SLA20T | SLA20TS2 | | |
| 1" | 25 | 13 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | SLA25V | SLA25VS2 | | |
| | 25 | 13 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | SLA25T | SLA25TS2 | | |
| 1-1/4" | 35 | 26 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | SLA35V | SLA35VS2 | | |
| | 35 | 26 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | SLA35T | SLA35TS2 | | |
| 1-1/2" | 35 | 26 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | SLA40V-35L | SLA40V-35LS2 | | |
| | 35 | 26 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | SLA40T-35L | SLA40T-35LS2 | | |
| 2" | 50 | 48 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | -- | SLA50VS2 | | |
| | 50 | 48 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | -- | SLA50TS2 | | |
| 1"F | 25 | 13 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | | 110 | 33 | 32 | -- | SLAF2V-25LS2 | | |
| | 25 | 13 | 0.5 | 25 | 20 | 25 | 20 | 20 | 20 | 10 | 185 | 30 | 25 | -- | SLAF2T-25LS2 | | |

Nr.Inreg.Com.J07/260/1998

C.I.F:RO 10825641

IBAN:RO07WBAN251100007500011

IBAN:RO66TREZ1165069XXX004921

INTESA SAN PAOLO BANK BT

TREZORERIA BOTOSANI

Str.Primaverii, Nr.2,Sc.B,Ap.2

Cod710070

Tel./Fax:0231.580535 M:0746.033.149

E-mail:primabotosani@yahoo.com

Web:www.primabt.ro

Web:www.robineti-proces.ro